

Vivitek D7180HD

FullHD Ultra Short-Throw Projector



Product Features

- Native 1080p resolution with a bright 3400 ANSI Lumens
- Delivers a large 86" to 97" image from a zero distance
- DLP® and BrilliantColor™ technologies for detailed image quality
- 6 segment wheel for exceptional color reproduction
- High-efficiency lamps that last up to 4000 hours
- Network ready for integration and system administration via RJ45
- Powerful 10W audio speaker
- Convenient top-loading lamp replacement design

Product Photos



Product Specifications

Display Type	DLP
Brightness	3400 ANSI Lumens
Native Resolution	1080p (1920 x 1080)
Maximum Resolution	1080p(1920 x 1080) @60Hz
Contrast Ratio	2500:1
Lamp Life and Type	3,000 /4,000 Hours (Boost/Std. Mode), 280W
Throw Ratio	0.19:1
Image Size (Diagonal)	86" - 97"
Projection Distance	22.4 ~ 62.3 mm (+/-10 mm)
Projection Lens	Manual Focus
Zoom Ratio	Fixed Lens
Aspect Ratio	16:9 Native, 4:3 & 16:10 Compatible
Offset	342mm ~ 440 mm (+/- 50 mm)
Keystone Correction	Vertical +/- 15°
Horizontal Frequency	15, 30 – 91.4kHz
Vertical Scan Rate	43 - 87Hz
Speakers	10W
Lens Shift Range	N/A
Video Compatibility	SDTV (480i/576i), EDTV (480p/576p), HDTV (720p, 1080i/p), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	HDMI v.1.3, VGA-In, DVI-D, Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RJ45, RS-232C, USB (Service)
Projection Method	Table Top, Wall-Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (H x D x W)	354 x 411 x 219 mm
Weight	9kg
Noise Level	30dB/37dB (Std. / Boost Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	310W (Eco Mode), 370W (Std. Mode), <1W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	Replacement Lamp, Remote

